

横断用製品は、蓋がかり部分が鋼製受け枠  
となります。又、ボルト締め付け型の騒音防  
止ゴム付グレーチングが標準仕様となります。

配筋表T-25縦断型(標準品)L=2000mm(側壁部は片側2m当り、頂版部<大梁部>は片側0.5m当りの数量)

呼 び 名	① 側 壁 主 筋		② 側 壁 配 力 筋		③ 大 梁 下 側 主 筋		④ 大 梁 配 力 筋		⑤ 大 梁 上 側 主 筋			
	径(mm)	本 数	径(mm)	本 数	径(mm)	本 数	径(mm)	本 数	径(mm)	本 数		
300×300	φ4.0	15	φ3.2	4	D10	4	φ4.0	6	D6	2		
400		16		5								
500		19		5								
600		14		5								
700		16		5								
800	17	5										
900	21	6		D10					3			
1,000	17	7										
1,100	20	7								D10	4	
1,200	20	9										
1,300	23	11										
1,400	D6	25	13	D10	3							
400×400	φ4.0	20	4			D13	3	φ4.0	12	D6	2	
500	φ5.0	23	5									
600		15	5									
700		19	5									
800		19	5									
900		21	6	D6	3							
1,000	18	6										
1,100	20	7	D6							4		
1,200	φ6.0	24		9								
500×500	φ5.0	19	φ3.2	4	D13					4	φ5.0	10
600		20		5								
700		14		5								
800		17		5								
900		19		6		D6	3					
1,000	φ6.0	18		6								
1,100	21	7		D6				4				
1,200	23	9										
1,300	D6	22		10		D6	4					
1,400		25		12				D6	5			
600×600		φ5.0	22	φ3.2	5	D13	4	φ6.0	14	D6	2	
700	16		5									
800	18		6		D6							3
900	20		7									
1,000	18		8									
1,100	φ6.0	20	8									
1,200	D6	22	10		D6					4		
1,300		23	12								D6	5
1,400		D10	24		12					D6	5	
1,500	12		φ4.0		14							

配筋表T-25横断型L=2000mm(側壁部は片側2m当り、頂版部<大梁部>は片側0.5m当りの数量)

呼 び 名	側 壁 部				大 梁 部																
	① 主 筋		② 配 力 筋		③ 下 主 筋		③' 上 主 筋		④ 下 配 力 筋		④' 上 配 力 筋										
	径(mm)	本 数	径(mm)	本 数	径(mm)	本 数	径(mm)	本 数	径(mm)	本 数	径(mm)	本 数									
300×300	φ5.0	21	φ3.2	4	D13	5	D10	4	φ5.0	5	φ4.0	4									
400		19		5																	
500		19		5																	
600		18		6																	
700		20		6																	
800	21	6																			
900	21	6																			
1,000	φ6.0	18		4									D13	6	D6	6	D6	4	φ4.0	4	
400×400	φ6.0	19		φ3.2																	5
500		19		5																	
600		18	6																		
700		20	6																		
800		D6	20	6																	
900	φ6.0	21	φ4.0	6																	
1,000		22	6																		
1,100		19	φ3.2	5	D13	6	D6	6	D6	5	φ4.0	5									
500×500	D6	19	5																		
600		19	5																		
700		18	6																		
800		20	6																		
900		20	6																		
1,000	φ6.0	21	φ4.0	6																	
1,100		21	6																		
1,200		22	6																		
1,300	φ6.0	23	φ5.0	7	D13	6	D6	6	D6	6	φ4.0	6									
1,400		24	7																		
600×600	φ6.0	19	φ3.2	5																	
700		18	6																		
800		20	6																		
900		20	6																		
1,000		21	6																		
1,100	φ6.0	21	φ4.0	6																	
1,200		22	6																		
1,300		23	6																		
1,400	D10	24	φ5.0	7	D6	6	D6	6	D6	6	φ4.0	6									
1,500		12	7																		

L=1000は、1/2の本数